





电机规格 Motor Specifications

电机型号 Motor Model	X2MM500A-B4LA
适配驱动器电压 V (rms) Typical Drive Voltages	380
直流母线电压 V (dc) Basic DC Bus Voltage	540
额定功率 kW Rated Output Power	5
额定转速 rpm Rated Speed	2000
最高转速 rpm Max. Speed	3000
额定转矩 Nm Rated Torque	23.9
堵转转矩 Nm Continuous Stall Torque	23.9
瞬时峰值转矩 Nm Peak Torque	71.6
额定电流 A (rms) Rated Current	13.5
堵转电流 A (rms) Continuous Stall Current	13.5
瞬时峰值电流 A (rms) Peak Current	45
线反电势常数 V (rms) / K rpm Voltage Constant	123.5
转矩常数 Nm / A (rms) Torque Constant	2.04
线电阻 Ω @20° C Winding Resistance (Line-Line)	0.41
线电感 mH (typ.) Winding Inductance (Line-Line)	8.5
转子惯量 kg m ² Inertia	80.8X10 ⁻⁴
电气时间常数 ms Electrical Time Constant	20.53
极对数 Rotor Poles	5
编码器 Encoder	17位绝对值
轴向载荷 N Shaft Load - Axial	343
径向载荷 N Shaft Load - Radial (End of Shaft)	784
防护等级 Protection Class	IP65
绝缘等级 Insulation Class	F
重量 kg Weight	24.1

制动器规格 Holding Brake Specifications

额定电压 DC(V) Rated Voltage	24±10%
额定电流 A Rated Current	1.04
静摩擦转矩(N.m) Static Friction Torque	> 74
吸引时间 ms Absorbing Time	≤ 120
释放时间 ms Releasing Time	≤ 30
释放电压 (V) Releasing Voltage	> 0.5



电机动力端 Motor Power Connection

针位 PIN No.	功能定义 Function
A	U
B	V
C	W
D	C, G

编码器端 Encoder Connection

针位 PIN No.	功能定义 Function
1	VCC
2	GND
3	-
4	BAT
5	+D
6	-D
7	-
8	-
9	BAT-
10	SHIELD




制动器端 Brake Connection

针位 PIN No.	功能定义 Function
1	BK
2	BK

备注:

notes

- GB/T 1096 键 B10x8x50 随电机一起包装, 但未安装。
GB/T 1096 Key B10x8x50 is shipped with motor, but not installed.
- 防护等级IP65(除了轴上没装油封和非密封连接器情况)。
IP65 (except Shaft without seal and non-sealed connectors)



标记	5	EC001380	ZML	120619
设计	ZML	062019	标准化	
审核				
工艺				



客户回签	
HCFA浙江禾川科技股份有限公司	
伺服电机(5kW带制动器)	
X2MM500A-B4LA	

阶段 标记 重量 比例
共 1 张 第 1 张