




电机型号 Motor Model	X2MM750A-B4LA
适配驱动器电压 V (rms) Typical Drive Voltages	380
直流母线电压 V (dc) Basic DC Bus Voltage	540
额定功率 kW Rated Output Power	7.5
额定转速 rpm Rated Speed	1500
最高转速 rpm Max. Speed	2500
额定转矩 Nm Rated Torque	47.8
堵转转矩 Nm Continuous Stall Torque	47.8
瞬时峰值扭矩 Nm Peak Torque	119
额定电流 A (rms) Rated Current	21.8
堵转电流 A (rms) Continuous Stall Current	21.8
瞬时峰值电流 A (rms) Peak Current	75
线反电势常数V (rms) / K rpm Voltage Constant	151
转矩常数Nm / A (rms) Torque Constant	2.5
线电阻 Ω @20° C Winding Resistance (Line-Line)	0.31
电感mH (typ.) Winding Inductance (Line-Line)	6.2
转子惯量kg m ² Inertia	114.2X10 ⁻⁴
电气时间常数ms Electrical Time Constant	20
极对数 Rotor Poles	5
编码器 Encoder	17位绝对值
轴向载荷 N Shaft Load - Axial	980
径向载荷 N Shaft Load - Radial (End of Shaft)	2058
防护等级 Protection Class	IP65
绝缘等级 Insulation Class	F
重量 kg Weight	29.7

額定电压 DC(V) Rated Voltage	24±10%
額定電流 A Rated Current	1.04
靜摩擦转矩(N.m) Static Friction Torque	> 74
吸引時間 ms Absorbing Time	≤ 120
釋放時間 ms Releasing Time	≤ 30
釋放电压 (V) Releasing Voltage	> 0.5





针位 PIN No.	功能定义 Function
A	U
B	V
C	W
D	CG

针位 PIN No.	功能定义 Function
1	VCC
2	GND
3	—
4	BAT
5	+D
6	—D
7	—
8	—
9	BAT—
10	SHIELD

针位 PIN No.	功能定义 Function
1	BK
2	BK

1. GB/T 1096 键 B12x8x90 随电机一起包装,但未安装。
GB/T 1096 Key B12x8x90 is shipped with motor, but not installed.

2. 防护等级IP65(除了轴上没装油封和非密封连接器情况)。
IP65 (except Shaft without seal and non-sealed connectors)



A3	6		EC001479	ZML	031720				
A2	5		EC001380	ZML	120619				
标记	处数	分区	更改文件号	签名	年月日				
设计	ZML	062019	标准化						
审核	曹云鹏	031720							
工艺			批准	李	2019.3.17				

共 1 张 第 1 张

客户回答

HCFA浙江禾川科技股份有限公司

伺服电机(7.5kW带制动器)

X2MM750A—B4LA